

U PVC Cable conduits of unplasticized polyvinyl chloride

Specification dn*en (mm)	Mean Outside Diameter de (mm)		Nominal wall thickness e _n (mm)		Solvent Cement Joints (SCJ)			Rubber Ring Joints (RRJ)		
	dn (mm)	Limit Deviation (mm)	Thickness (mm)	Limit Deviation	Depth of Socket L (mm)	Mean inner diameter in the middle of		Minimum socket length A _{min} (mm)	First stage minimum length of socket B _{min} (mm)	Minimum ID of socket in second stage d _{imin} (mm)
						Min (mm)	Max (mm)			
50*2.0	50	-0.3 +0.6	2.0	-0.2 +0.3	60	49.8	50.7			
50*2.8	50	-0.3 +0.6	2.8	-0.3 +0.3						
50*5.0	50	-0.3 +0.6	5.0	-0.5 +0.5						
63*5.0	63	-0.3 +0.6	5.0	-0.5 +0.5	65	62.8	63.7			
75*2.3	75	-0.3 +0.6	2.3	-0.2 +0.2	70	74.8	75.7			
75*2.8	75	-0.3 +0.6	2.8	-0.3 +0.3						
75*5.0	75	-0.3 +0.6	5.0	-0.5 +0.5						
90*2.8	90	-0.3 +0.6	2.8	-0.3 +0.3	70	89.8	90.7			
90*3.2	90	-0.3 +0.6	3.2	-0.3 +0.3						
90*4.5	90	-0.3 +0.6	4.5	-0.4 +0.4						
110*3.0	110	-0.4 +0.8	3.0	-0.3 +0.3				100	60	111.0
110*4.0	110	-0.4 +0.8	4.0	-0.4 +0.4						
110*5.0	110	-0.4 +0.8	5.0	-0.5 +0.5						
110*7.0	110	-0.4 +0.8	7.0	-0.7 +0.7						
160*3.2	160	-0.5 +1.0	3.2	-0.3 +0.3				120	60	161.2
160*4.0	160	-0.5 +1.0	4.0	-0.4 +0.4						
160*5.0	160	-0.5 +1.0	5.0	-0.5 +0.5						
160*8.0	160	-0.5 +1.0	8.0	-0.8 +0.8						
167*5.0	167	-0.5 +1.0	5.0	-0.5 +0.5				140	60	168.5
167*6.0	167	-0.5 +1.0	6.0	-0.6 +0.6						
167*8.0	167	-0.5 +1.0	8.0	-0.8 +0.8						
167*8.5	167	-0.5 +1.0	8.5	-0.8 +0.8						
192*5.8	192	-0.5 +1.0	5.8	-0.6 +0.6				160	60	193.8
192*6.5	192	-0.5 +1.0	6.5	-0.6 +0.6						
192*7.5	192	-0.5 +1.0	7.5	-0.7 +0.7						
192*8.5	192	-0.5 +1.0	8.5	-0.8 +0.8						
200*4.0	200	-0.5 +1.0	4.0	-0.4 +0.4				180	60	202.0
200*5.0	200	-0.5 +1.0	5.0	-0.5 +0.5						
200*6.0	200	-0.5 +1.0	6.0	-0.6 +0.6						
200*8.0	200	-0.5 +1.0	8.0	-0.8 +0.8						
200*9.0	200	-0.5 +1.0	9.0	-0.9 +0.9						
200*10.0	200	-0.5 +1.0	10.0	-0.9 +0.9						

Cable conduits of chlorinated polyvinyl chloride

Specification dn*en (mm)	Mean Outside Diameter		Nominal wall thickness		Minimum socket length A _{min} (mm)	First stage minimum length of socket B _{min} (mm)	Minimum ID of socket in second stage d _{imin} (mm)
	dn (mm)	Limit Deviation (mm)	Thickness (mm)	Limit Deviation			
110*5.0	110	+0.8	5.0	+0.5	100	60	111.0
139*6.0	139	+0.8	6.0	+0.5	120		140.2
167*6.0	167	+0.8	6.0	+0.5	140		168.5
167*8.0	167	+1.0	8.0	+0.6			
192*6.5	192	+1.0	6.5	+0.5	160		193.8
192*8.5	192	+1.0	8.5	+0.6			
219*7.0	219	+1.0	7.0	+0.5	180		221.0
219*9.5	219	+1.0	9.5	+0.8			

Note: Other specifications can be produced according to customer requirements.
 The color is usually orange red.

